

48B Programmable Control Panel



48B Programmable Control Panel

48B programmable control panels are designed to control all series of routing switchers. The panels include 48 keys configurable for different functions. A certain input or output channel of a routing switcher can be assigned to a button for direct switching operation. 48B programmable control panels are used with X+Y or MP series panels for partial control of the assigned input/output channels to prevent any inadvertent operations to the other channels.

SPECIFICATIONS

Specifications are subject to change without notice.

CONTROL INTERFACE

RS-232/422.....	DB-9F (x1)
CAN-BUS.....	RJ-45 (x2)
C-BUS.....	BNC (x2)
RS-485.....	RJ-45 (x1)
LAN.....	RJ-45 (x1)
GPI/O.....	DB-25 (x1)

MECHANICAL

Width.....	19 in. (483 mm)
Height.....	1RU (44 mm)
Depth.....	4.76 in. (121 mm)

KEY FEATURES AND BENEFITS

Frame

- 19", 1RU
- 48 programmable keys
- Gain access to any routing switchers

Control and power supply

- Support multiple frame cascading
- Controls with C-BUS, CAN-BUS, LAN, RS-485 and RS-232/422
- GPI triggering
- Redundant power supplies

ELECTRICAL

Power Supply.....	90 ~ 260 V AC, 50/60 Hz
Power Consumption.....	3 W

ENVIRONMENTAL

Operating Temperature.....	32° ~ 104° F (0° ~ 40° C)
Relative Humidity.....	10% ~ 90%