

MCP-1600 Master Control Panel

MCP-1600 Master Control Panel is designed to control the broadcast routing switch BHR-1600. It provides PST, PGM and eight auxiliary outputs. Various transitions at different transition rates and full control of embedded audio are available.

KEY FEATURES AND BENEFITS

Frame

- 19", 1RU
- Control BHR-1600 routing switch
- Supports switching of PST, PGM and 8 auxiliary outputs
- Transitions include cross-fade, V-fade, fade-cut, cut-fade and
- Full control of embedded audio
- Video and audio transition speed control
- Controls with C-BUS, CAN-BUS, LAN, RS-485 and RS-232/422
- GPIO triggering
- Redundant power supplies

SPECIFICATIONS

Specifications are subject to change without notice.

CONTROL INTERFACE

RS-232/422	DB-9F (×1)
CAN-BUS	RJ-45 (×2)
C-BUS	BNC (×2)
RS-485	RJ-45 (×2)
LAN	RJ-45 (×1)
GPI/O	DB-25 (×1)

MECHANICAL

Width	19 in. (483 mm)
Height	1RU (44 mm)
Depth	4.76 in. (121 mm)

ELECTRICAL

Power Supply	90 ~ 260 V AC, 50/60 H	lz
Power Consumption	3 W	

ENVIRONMENTAL

Operating Temperature	32° ~ 104° F (0° ~ 40° C)
Relative Humidity	10% ~ 90%