

MP-16 & MP-32 Direct Switch Control Panel



MP-16



MP-32

KEY FEATURES AND BNEFITS

Frame and sizes

- 19", 1RU
- Size available up to 16x16 (MP-16)/32x32 (MP-32)
- Separate source select keys and destination select keys
- Direct switch control
- DIP switch configurable for panel address
- Breakaway switching and AFV
- Individual Lock key

MP Series Direct Switch Control Panel

MP series direct switch control panels are designed to control small and medium (16x16/32x32 and down) routing switchers. Each button represents one input or output channel. Switching is controlled by directly selecting the input/output channel key.

The panels include intuitive 16/32 destination select keys and 16/32 source select keys for direct switch and three LEDs for involved level indication. Video and audio can be switched separately and AFV is also available. Destination lock allows locking of a router destination, preventing any panel from changing the source connected to the destination.

Control and power supply

- Support multiple frame cascading
- Controls with C-BUS, CAN-BUS, LAN, RS-485 and RS-232/422
- GPI triggering
- Redundant power supplies

SPECIFICATIONS

Specifications are subject to change without notice.

CONTROL INTERFACE

RS-232/422.....	DB-9F (x1)
CAN-BUS.....	RJ-45 (x2)
C-BUS.....	BNC (x2)
RS-485.....	RJ-45 (x1)
LAN.....	RJ-45 (x1)
GPI/O.....	DB-25 (x1)

ELECTRICAL

Power Supply.....	90 ~ 260 V AC, 50/60 Hz
Power Consumption.....	3 W

ENVIRONMENTAL

Operating Temperature.....	32° ~ 104° F (0° ~ 40° C)
Relative Humidity.....	10% ~ 90%

MECHANICAL

Width.....	19 in. (483 mm)
Height.....	1RU (44 mm)
Depth.....	4.76 in. (121 mm)